CCN 47830530001 Rev B ECN 150430



## COMPRESSOR DATA SHEET

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Fixed Speed** 

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Gardner Denver						
	Model Number PureAir T132	Date:	March 2024				
2	X Air-cooled Water-cooled	Type:	Screw				
	Oil Injected X Oil-Free	# of Stages:	2				
3*	Rated Capacity at Full Load Operating Pressure a, e	750	acfm <sup>a, e</sup>				
4	Full Load Operating Pressure <sup>b</sup>	145	psig <sup>b</sup>				
5	Maximum Full Flow Operating Pressure <sup>c</sup>	155	psig <sup>c</sup>				
6	Drive Motor Nominal Rating	175	hp				
7	Drive Motor Nominal Efficiency	95.4%	percent				
8	Fan Motor Nominal Rating (if applicable)	10.1	hp				
9	Fan Motor Nominal Efficiency	92.1%	percent				
10*	Total Package Input Power at Zero Flow <sup>e</sup>	25.7	kW <sup>e</sup>				
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>		$kW^d$				
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>	20.21	kW/100 cfm <sup>e</sup>				

<sup>\*</sup> For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator.

Consult CAGI website for a list of participants in the third party verification program: <a href="https://www.cagi.org">www.cagi.org</a>

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

## Member:



- b. The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below.
   NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate <sup>f</sup>	Specific Energy <sup>g</sup> Consumption	No Load / Zero Flow Power <sup>e</sup>
m <sup>3</sup> /min	ft <sup>3</sup> / min	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 030.2

1/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.