Part No. 47830519001 ECN 1519819



## COMPRESSOR DATA SHEET

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Fixed Speed** 

MODEL DATA - FOR COMPRESSED AIR						
1	Manufacturer: Gardner Denver					
	Model Number PureAir T110-W110 (NA-IP55)	Date:	August 2024			
2	Air-cooled X Water-cooled	Type:	Screw			
	Oil Injected X Oil-Free	# of Stages:	2			
3*	Rated Capacity at Full Load Operating Pressure a, e	756	acfm <sup>a, e</sup>			
4	Full Load Operating Pressure <sup>b</sup>	100	psig <sup>b</sup>			
5	Maximum Full Flow Operating Pressure <sup>c</sup>	110	psig <sup>c</sup>			
6	Drive Motor Nominal Rating	150	hp			
7	Drive Motor Nominal Efficiency	95.0%	percent			
8	Fan Motor Nominal Rating (if applicable)	1.2	hp			
9	Fan Motor Nominal Efficiency	82.5%	percent			
10*	Total Package Input Power at Zero Flow <sup>e</sup>	24.8	kW <sup>e</sup>			
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup> 129.8		$kW^d$			
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>	kW/100 cfm <sup>e</sup>				

<sup>\*</sup> For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

## Member:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions
- b. The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate <sup>f</sup>	Specific Energy <sup>g</sup> Consumption	No Load / Zero Flow Power <sup>e</sup>
m <sup>3</sup> /min	ft <sup>3</sup> / min	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 030.2

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data. 12/19 Rev 3